



Specifications Ledvance LED
Downlight Comfort Aluminium White
42W 5000lm 55D - 930-940 CCT |
265mm - Cutout 250mm - IP44 - Best
Colour Rendering - UGR<19 - Zigbee
Dimmable

[View Product](#)

General Information

| | |
|--------------------------|---|
| SKU | 257977 |
| EAN | 4099854620430 |
| Brand | Ledvance |
| Manufacturer Name | DL CMFT ZB D250 P 42W 93040 U19 WT LEDV |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 100000 |

Technical Information

| | |
|-----------------------------|--------------------------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Ecosystem Compatibility | Ledvance Direct Easy, Vivares Zigbee |
| Lighting Control | Zigbee |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable with Zigbee |
| Colour Code | 930 Warm White, 940 Cool White |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra) | 90-99 |
| Colour of Light | White |

| | |
|--------------------------|---------------|
| Light colour options | Single Color |
| Beam Angle (degree) | 55 |
| Luminous Efficacy (lm/W) | 119 |
| Power factor | >0.90 |
| Unified Glare Rating | < 30 |
| Optical Cover | Opal |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|--------------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 250 |
| IP-rating | IP44 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Series | DOWNLIGHT COMFORT ZIGBEE UGR19 |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 124 |
| Diameter (mm) | 265 |

Sensor Information

Type of sensor

Why Any-lamp?

No Sensor



Order from the **largest lighting specialist** in Europe



Customised quotation



Up to **7 years warranty**



Easy return process